This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(22) International Filing Date: 17 May 1991 (17.05.91) (30) Priority data: 535,932 11 June 1990 (11.06.90) US (71) Applicant: SCHNEIDER (USA) INC. [US/US]; 5905 Nathan Lane, Plymouth, MN 55442 (US). (72) Inventor: SHOCKEY, Rick, L.; 3890 Westbury Drive, Eagan, MN 55123 (US).	(51) International Patent Classification 5: A61M 29/00, 25/01	A1	(11) International Publication Number: WO 91/19528 (43) International Publication Date: 26 December 1991 (26.12.91)
(71) Applicant: SCHNEIDER (USA) INC. [US/US]; 5905 Nathan Lane, Plymouth, MN 55442 (US). Published With international search report. (72) Inventor: SHOCKEY, Rick, L.; 3890 Westbury Drive, Eagan, MN 55123 (US). (74) Agents: RICHARDSON, Peter, C. et al.: Pfizer Inc. 235	(22) International Filing Date: 17 May 1991 (30) Priority data:		pean patent), CA, CH (European patent), AC, BE (European patent), DE, DE (Utility model), DE (European patent), DK (European patent), GE (European patent), GR (European patent) TT (European patent)
74) Agents: RICHARDSON, Peter, C. et al.: Pfizer Inc. 235	71) Applicant: SCHNEIDER (USA) INC. [US/US]; than Lane, Plymouth, MN 55442 (US). 72) Inventor: SHOCKEY, Rick, L.; 3890 Westbury E	5905 N	Published With international search report.
	74) Agents: RICHARDSON, Peter, C. et al.: Pfizer	Inc., 23	5

(54) Title: TRACKING GUIDEWIRE



(57) Abstract

A guidewire and guidewire assembly (10) for placement within a blood vessel for penetrating an occlusion therein. The guidewire comprises a length of flexible wire (12) having a concentric lumen (14) running its entire length and a distal end portion (20) having an arcuate tip (22) and a diameter greater than that of the wire immediately proximal thereto. The guidewire assembly comprises the guidewire described along with a flexible stylet (32) substantially the same length as the flexible wire and disposed within the lumen of the wire. In operation, the distal end portion is positioned in the blood vessel against an occlusion, and a dottering action is thereafter provided whereby the distal end portion repeatedly impinges on the occlusion until penetration of the occlusion occurs.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT AU BB BE BF BC CF CG CH CI CM DE	Austria Australia Barbados Belgium Burkina Paso Bulgaria Benin Brazil Canada Central African Republic Congo Switzerland Côtte d'Ivoire Cameroon Czechoslovakia Germany Denmark	ES FI FR GA GB GR HU IT JP KP LI LK LU MC	Spain Finland France Gabon United Kingdom Guinea Greece Hungary Italy Japan Democratic People's Republic of Korea Republic of Korea Litechtenstein Srl Lanka Luxembourg Monaco	MG ML MN MR MW NL NO PL RO SD SE SN TD TG US	Madagascar Mali Mongolia Mauritania Matawi Netherlands Norway Poland Romania Sudan Sweden Senegal Societ Union Chad Togo United States of America
-------------------------------------	--	--	--	--	---

-1-

TRACKING GUIDEWIRE Technical Field

This invention relates generally to a tracking guidewire, and in particular to an occlusion-penetrable guidewire having a lumen throughout its entire length into which a stylet can be inserted, and having a distal end portion with an arcuate tip and a diameter greater than that of the immediately proximal wire.

Background Art

10 Vessel entry for treatment of certain untoward health conditions is a common practice. Such entry can include insertion into a blood vessel of a guidewire whose distal end is expected to reach a certain site within the body and have utility thereafter as 15 required. Many times, however, a blood vessel may be completely or almost completely occluded, thereby rendering it substantially impossible to advance a guidewire there beyond to a designated site without first employing a separate procedure to remove the occlusion.

It is therefore a primary object of the present invention to provide a guidewire having a lumen running its entire length and a distal end portion capable of penetrating a vascular occlusion. Another object of the present invention is to provide such a guidewire wherein the tip of the distal end portion is arcuate and the diameter of the distal end portion is greater than that of the immediately proximal wire. Yet another object of the present invention is to provide a guidewire assembly wherein a stylet can be removably inserted into the length of the guidewire lumen to thereby enhance guidewire structure. These and other objects will become apparent throughout the description which now follows.

Disclosure of Invention

The present invention is a guidewire for placement within a blood vessel for penetrating an occlusion in the vessel. The guidewire comprises a length of 5 flexible wire having a concentric lumen running its entire length. At its proximal end the wire has a hub opening to the lumen, and at its distal end it has a distal end portion which has an arcuate tip and a diameter greater than the diameter of the wire 10 immediately proximal thereto. The invention additionally includes a guidewire assembly which comprises the guidewire and a flexible stylet substantially the length of the wire for removable insertion into the lumen of the wire for substantially 15 its entire length. Such stylet placement provides a greater stiffness and structural integrity to the guidewire.

Finally a method of penetrating an occlusion in a blood vessel comprises inserting the guidewire or guidewire assembly into an occluded blood vessel and positioning the arcuate tip of the distal end portion against the proximal wall of the occlusion. After such positioning, a dottering action is provided to the guidewire or guidewire assembly for a sufficient period of time whereby the repeated impingement upon the occlusion results in penetration thereof. Once the distal portion of the guidewire or guidewire assembly has passed through the occlusion, and the stylet has been withdrawn in the case of the guidewire assembly, a contrast medium can be injected into the lumen to confirm guidewire positioning within the vessel.

Brief Description of Drawings

Presently preferred embodiments of the invention are illustrated in the accompanying drawings in which:

WO 91/19528 PCT/US91/03509

-3-

Figure 1 is a side elevation view of a guidewire; Figure 2 is a side elevation view partially in section of a quidewire assembly;

Figure 3 is a side elevation view of a stylet: Figure 4 is a side elevation view of a second embodiment of a distal end of a quidewire; and

5

10

Figure 5 is a side elevation view of a third embodiment of a distal end of a quidewire.

Modes for Carrying Out the Invention

Referring to Figure 1, a guidewire 10 illustrated. The guidewire 10 comprises a length of flexible wire 12 having a concentric lumen 14 running the entire length of the wire 12 and a proximal end hub 18 which opens to the lumen 14. The opposite end of 15 the wire 12 has a distal end portion 20 which has an arcuate tip 22 and a diameter greater than the diameter of the wire 12 immediately proximal to the end portion 20. The guidewire 10 can be conventionally constructed of metal core, and is preferably constructed of metal 20 coils.

Figure 2 illustrates a guidewire assembly 30 comprising a guidewire 10, as shown in Figure 1, and a flexible stylet 32, as shown in Figure 3, disposed within the lumen 14 of the wire 12. The stylet 32 is 25 substantially the length of the wire 12 additionally has a proximal end member 34 whose shape is complimentary to the interior wall 36 of the hub 18. The hub 18 is provided with locking means such as conventional Luer locking threads which securely 30 maintains the stylet 32 within the lumen 14, yet provides releasability for withdrawal of the stylet 32 as required. The stylet 32 can be constructed of metal or polymer core, and is preferably constructed of metal.

WO 91/19528 PCT/US91/03509

-4-

As earlier noted, the distal end portion 20 of the wire 12 has an arcuate tip 22 and has a diameter which is greater than that of the wire 12 immediately proximal thereto. Three non-limiting examples of 5 preferred shapes of the end portion 20 are illustrated in Figures 1, 2, 4 and 5. Specifically, Figures 1 and 2 show an arrow shape 40; Figure 4 shows an elliptical shape 42; and Figure 5 illustrates a tear-drop shape It is to be understood, of course, that shapes 10 other than those illustrated can be employed as long as an arcuate tip is provided to thereby enhance physical intrusion of an occlusion. The various shapes of the respective distal end portions are attained in the manufacturing process which can include EDM machining 15 and grinding.

In operation, the guidewire 10, and in particular its distal arcuate tip 22 and distal end portion 20, functions to penetrate an occlusion in a blood vessel. The user inserts the guidewire 10 into a blood vessel 20 and positions the arcuate tip 22 against the proximal wall of an occlusion. Once placed, the guidewire 10 is subjected to a dottering action by the user to effectuate a repeated impinging action upon the occlusion by the distal end portion 20 for a period of 25 time sufficient to penetrate the entire length of the occlusion and thereby permit continued travel of the guidewire 10 itself or of other apparatus. Should an occlusion exhibit a resistance too great to permit the guidewire 10 alone to penetrate, the stylet 32 is 30 inserted into the length of the lumen 14 and locked into place. The inserted stylet 32 provides a greater stiffness and structure to the guidewire 10, thereby providing a more aggressive impingement action on the occlusion during dottering to accomplish penetration

WO 91/19528 PCT/US91/03509

-5-

thereof. Once the distal end portion 20 of the guidewire 10 is through the stenosis, the stylet 32 can be removed from the lumen 14 and a contrast medium can injected into the lumen 14 to thereby confirm the true position of the distal end portion 20.

While an illustrative and presently preferred embodiment of the invention has been described in detail herein, it is to be understood that the inventive concepts may be otherwise variously embodied and employed and that the appended claims are intended to be construed to include such variations except insofar as limited by the prior art.

WO 91/19528 PCT/US91/03509

-6-

CLAIMS

1) A guidewire assembly (10) for placement within a blood vessel for penetrating an occlusion therein, the guidewire assembly (10) comprising:

ð


a) a length of flexible wire (12) having a concentric lumen (14) running the entire length of the wire (12), with said wire (12) having a proximal end hub (18) opening to the lumen (14) and a distal end portion (20) having an arcuate tip (22) and a diameter greater than the diameter of the wire (14) immediately proximal thereto; and

- b) a flexible stylet (32) substantially the length of the wire (12) and additionally having a proximal end member (34) complimentarily shaped to the interior wall (36) of the hub (18), said stylet (32) having a diameter less than the diameter of the lumen (14) of the wire (12) and removably insertable within the lumen (14) substantially throughout the entire length of said lumen (14).
- 2) A guidewire assembly (10) as claimed in claim 1 and having in addition locking means disposed at the proximal end hub (18) opening of the wire (12) for releasably securing the proximal end member (34) of the stylet (32) within at least a portion of the hub (18).
- 25 3) A guidewire assembly (10) as claimed in claim 2 wherein the distal end portion (20) of the wire (12) is in the shape of an arrow (40).
- 4) A guidewire assembly (10) as claimed in claim
 2 wherein the distal end portion (20) of the wire (12)
 30 is in the shape of an ellipse (42).
 - 5) A guidewire assembly (10) as claimed in claim 2 wherein the distal end portion (20) of the wire (12) is in the shape of a tear drop (44).
 - A guidewire assembly (10) as claimed in claim


1 wherein the distal end portion (20) of the wire (12) is in the shape of an arrow (40).

- 7) A guidewire assembly (10) as claimed in claim 1 wherein the distal end portion (20) of the wire (12) 5 is in the shape of an ellipse (42).
 - 8) A guidewire assembly (10) as claimed in claim 1 wherein the distal end portion (20) of the wire (12) is in the shape of a tear drop (44).


1/2



SUBSTITUTE SHEET







SUBSTITUTE SHEET

I. CLAS	SIFICATION OF SUBJ	ECT MATTER (if several classificat	ion symbols and a fallone and		
Accord	ing to International Pater	t Classification (IPC) or to both Nation	nal Classification and IDC		
Int	C1. 5	A61M29/00 ; A61M25	/01		
1		•		••	
IL FIEL	DS SEARCHED				
	•	Minimum Do	comentation Searched?		
Classific	cation System		Classification Symbols		
Int	.C1. 5	A61M; A61B			
		Documentation Searched at	ber than Minimum Documentation		
		to the Extent that such Document	ats are included in the Fields Searched		
Ì					
III. DOCI	JMENTS CONSIDERE	TO BE RELEVANT			
Category °	Citation of Do	cument, 11 with indication, where appro	priate, of the relevant passages 12	Relevant to Claim No.13	
Y	US,A,3 1	96 876 (MILLER M.) Ju	uly 27, 1965	1-2,4-5.	
	con alad			7-8	
	See Clair	m; figures 1-4			
Y	US.A.4 3	88 076 (WATERS) June	14 1093	1-2 4 5	
		and (mileto) odile	14, 1303	1-2,4-5, 7-8	
	see abst	ract; figures 1-5		'-0	
A	ED 4 363	661 (ADVANCED CARDIO			
A	INC) An	1-2			
	see abst	ril 18, 1990 ract; figures 2-4			
	see colum	nn 3, line 52 - line	54		
•	FR,A,2 29	0 917 (LINDEMANN) Ju	ne 11, 1976	3-8	
	see page	4, line 19 - line 29	; figures 2-3	1	
\ l	US.A.3 99	9 551 (SPITZ ET AL.)	Document 29 1076		
`	see colum	n 3, line 36 - line	December 28, 1976 17: figures 2 4	3,6	
1			f, ligures L, T		
° Special.	categories of cited docum	10			
			"I" later document published after the interna or priority date and not in conflict with th	e annication but	
considered to be of particular relevance cated to understand the principle or theory underlying the					
"E" earlier document but published on or after the international filing date "X" focument of particular relevance; the claimed invention cannot be considered to					
ward:	I TO COLORS LO ESCAPOTAD ED 6	ubts on priority claim(s) or publication date of another	involve an inventive step	1	
CICEU	ou or other thecisi terror	i (25 specified). disclosure, use, exhibition or	Y document of particular relevance; the claim cannot be considered to involve an inventi-	e step when the	
orner	DICELES .		focument is combined with one or more of ments, such combination being obvious to	her such docu- a person skilled	
	than the priority date cla	se international filing date but imed	in the art. "&" document member of the same patent fami		
. CERTIFI	CATION				
	tual Completion of the L	ternational Search	Date of Melling of this International		
	30 JUL		Date of Mailing of this International Search	жероп	
		.1 1331	15, 89, 91		
ernational S	exching Authority		Signature of Authorized Officer		
	EUROPEAN F	PATENT OFFICE	MIR Y GUILLEN V.	the !	
				/	

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

PCT/US 91/03509

SA 47937

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are surrely given for the purpose of information.

30/07/91

cited in search report	Publication date	Patent family member(s)		Publication date	
US-A-3196876		None			
US-A-4388076	14-06-83	US-E-	RE32306	16-12-86	
EP-A-363661 	18-04-90	US-A- JP-A-	4917102 2191467	17-04-90 27-07-90	
FR-A-2290917	11-06-76	DE-A- CH-A- US-A-	2454351 591254 4013079	20-05-76 15-09-77 22-03-77	
US-A-3999551	28-12-76	None	* *** * * * * * * * * * * * * * * * *	- 4 4 8 6 8 7 7 7 7 7 7 8 8 8 8 8 8 8 8 8 8 8	

For more details about this assex : see Official Journal of the European Patent Office, No. 12/82